

AMENDMENTS TO THE CLAIMS:

Please amend the claims in this reissue application as follows:

7. (Canceled)

9. (Canceled)

11. (Twice Amended) A cemented carbide cutting portion adapted to be connected to a tool body for rotary metal cutting, comprising a front cutting surface having at least one cutting edge, a rear support surface, and at least one chip flute formed in a side surface of the cutting portion for guiding cuttings, said cutting portion including coupling means defining a dovetail-shaped projection and forming part of a bayonet coupling adapted to connect a tool body with the cutting portion with a slide fit to an elastically deflecting portion of the tool body.

12. (Canceled)

14. (Twice Amended) A method of attaching a drilling head to a drill body, said drill body having a longitudinal axis and first and second opposed ends, one of said opposed ends comprising a centrally disposed dovetail-shaped recess, and at least two circumferentially spaced projections, each of said projections having a stop surface; said drilling head made of cemented carbide and having first and second opposed ends, one of said opposed ends comprising a cutting portion, and the other of said opposed ends

comprising a dovetail-shaped projection, said drilling head further comprising at least one stop surface; wherein said method comprises:

inserting said dovetail-shaped projection into said dovetail-shaped recess; and
rotating said drilling head relative to said drill body such that a slide fit is formed between the drilling head and the drill body by elastic deflection of said projections, and the at least one stop surface on said drilling head comes into engagement with at least one of the stop surfaces on one of the projections.

16. (Amended) A rotary metal-cutting tool comprising, in combination, a tool body and a cutting portion attached to the tool body:

the tool body comprising a shank portion defining a longitudinal center axis and rear chip flutes formed in an external side surface for guiding chips rearwardly during a cutting operation;

the cutting portion comprising a front cutting surface and front chip flutes formed in a side surface of the cutting portion and intersecting the cutting face to form cutting edges therewith;

the tool body and cutting portion being interconnected by a dovetail-shaped bayonet coupling formed by projections disposed on one of the tool body and cutting portion, and recesses formed in the other of the tool body and cutting portion, the projections being circumferentially offset with respect to the flutes and extending generally longitudinally, the recesses extending circumferentially from respective flutes, the flutes sized to longitudinally receive respective projections during longitudinal insertion or removal of the cutting portion relative to the tool body, the cutting portion being rotatable about the center axis relative to

the tool body to transfer the projections from the respective flutes into the recesses with a slide fit, while bringing the front and rear flutes into mutual alignment.

17. (Amended) The tool according to claim 16, wherein the slide fit produces elastic deflection of the projections.

18. (Amended) A rotary metal-cutting tool comprising, in combination, a tool body and a cutting portion attached to the tool body:

the tool body comprising a shank portion defining a longitudinal center axis and rear chip flutes formed in an external side surface for guiding chips rearwardly during a cutting operation;

the cutting portion comprising a front cutting surface and front chip flutes formed in a side surface of the cutting portion and intersecting the cutting face to form cutting edges therewith;

the tool body and cutting portion being interconnected by a dovetail-shaped bayonet coupling formed by projections disposed on one of the tool body and cutting portion, and recesses formed in the other of the tool body and cutting portion, the projections being circumferentially offset with respect to the flutes, the recesses extending circumferentially from respective flutes, the flutes sized to receive respective projections during insertion or removal of the cutting portion relative to the tool body, the bayonet coupling further comprising a first oblique surface and a second oblique surface, the cutting portion being rotatable about the center axis relative to the tool body to transfer the projections from the respective flutes into the recesses with a slide fit between the first and second oblique surfaces, while bringing the front and rear flutes into mutual alignment.

19. (Amended)The tool according to claim 18, wherein the slide fit produces
elastic deflection of the projections.